Pilot-in-the-loop Method Development

2012 Basic and Applied Research in Sea-Based Aviation

ONR #BAA12-SN-0028

REPORT No. 8/C576

PERIOD 20 April 2014 to 20 May 2014

Prepared by

Combustion Research and Flow Technology, Inc. (CRAFT Tech)

6210 Keller's Church Rd. Pipersville, PA 18947

Phone: 215/766-1520; Fax: 215/766-1524

Attn: J. Shipman

Email: shipman@craft-tech.com

20 May 2014

Prepared for

Naval Air Warfare Center AD 48110 Shaw Road, Code 4.3.2.1 Patuxent River, MD 20670 Arlington, VA 22203-1995

Attn: Dr. Susan Polsky, Code 4.3.2.1

Phone: 301.342.8575

Email: susan.polsky@navy.mil

Prepared under

Contract Number: N00014-13-C-0456

PERIOD: 20 September 2013 to 20 September 2016

DISTRIBUTION STATEMENT A: Distribution Approved for public release; distribution is unlimited.

maintaining the data needed, and c including suggestions for reducing	lection of information is estimated to ompleting and reviewing the collect this burden, to Washington Headqu uld be aware that notwithstanding and DMB control number.	tion of information. Send commentarters Services, Directorate for Inf	ts regarding this burden estimate formation Operations and Reports	or any other aspect of the property of the pro	nis collection of information, Highway, Suite 1204, Arlington	
1. REPORT DATE 20 MAY 2014		2. REPORT TYPE		3. DATES COVE 20-04-2014	tred to 20-05-2014	
4. TITLE AND SUBTITLE				5a. CONTRACT NUMBER		
Pilot-in-the-loop Method Development				5b. GRANT NUMBER		
			5c. PROGRAM ELEMENT NUMBER			
6. AUTHOR(S)	5d. PROJECT NUMBER			JMBER		
				5e. TASK NUMBER		
		5f. WORK UNIT NUMBER				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Combustion Research and Flow Technology, Inc. (CRAFT Tech),6210 Keller?s Church Rd,Pipersville,PA,18947				8. PERFORMING ORGANIZATION REPORT NUMBER		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) 10. SPONSOR/MONITOR'S			ONITOR'S ACRONYM(S)			
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)		
12. DISTRIBUTION/AVAII Approved for publ	ABILITY STATEMENT ic release; distribut	ion unlimited				
13. SUPPLEMENTARY NO	OTES					
14. ABSTRACT						
15. SUBJECT TERMS						
16. SECURITY CLASSIFIC	6. SECURITY CLASSIFICATION OF:			18. NUMBER	19a. NAME OF	
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified	ABSTRACT Same as Report (SAR)	OF PAGES 8	RESPONSIBLE PERSON	

Report Documentation Page

Form Approved OMB No. 0704-0188

Pilot-in-the-loop Method Development

2012 Basic and Applied Research in Sea-Based Aviation ONR #BAA12-SN-0028

PERIOD 20 April 2014 to 20 May 2014

1 PROJECT OVERVIEW

The goal of this project is to integrate novel numerical modeling and computer hardware approaches to compute the non-linear aerodynamic coupling between the ship and aircraft in such a way that execution times are at real-time speeds, allowing for pilot-in-the-loop CFD to be integrated in the piloted flight simulation environment. To achieve the speed gains required, three areas will be targeted for implementation into the CFD simulation framework: (1) numerical algorithms, (2) novel domain boundaries, and (3) Graphical Processing Unit (GPU) hardware. A framework will be established to link the CFD with realtime simulations. A building block approach will be employed to first demonstrate non-realtime integration of the CFD simulation framework with helicopter flight dynamic models, then realtime execution for a minimum fidelity airwake/aircraft simulation, then build to higher fidelity realtime simulations.

1.1 Project Technical Objectives

The project involves the following seven tasks to accomplish the technical objectives of the project:

- Task 1: Implement modular implicit/explicit solver
- Task 2: Apply structured numerics
- Task 3: Apply subdomain with immersed boundary
- Task 4: Implement higher order explicit solver for GPU execution
- Task 5: Integrate with the GENHEL-PSU flight dynamics model
- Task 6: Demonstrate flight simulation in the PSU Rotorcraft Simulation Facility
- Task 7: Demonstrate flight Simulation in NAVAIR Manned Flight Simulator

2 WORK SUMMARY

A full scale SFS2 (Simple Frigate Shape) grid was constructed based on the wind tunnel grids provided by NAVAIR. The case was tested and setup with example inputs and provided to PSU. Currently PSU researchers are generating unsteady airwake solutions on the grid using CRUNCH CFD for coupling with the GENHEL UH-60 helicopter model.

An LHD geometry was provided to CRAFT Tech for completing structured simulations for Task 2. A slightly simplified geometry was built from this model and an initial unstructured grid was constructed for running CRUNCH airwake simulations. These cases are currently underway and we are beginning to construct structured grids of the LHD case.

2.1 Full-Scale SFS2 Cases

A full-scale SFS2 grid was generated with Pointwise from the wind tunnel grids (1/100th scale) provided by NAVAIR by extracting the surface mesh and scaling up to full scale. A farfield boundary was created in place of the wind tunnel walls. The original subscale grids were created with the VGRID grid generator. Care was taken to match as closely as possible grid parameters such as edge length and wall spacing given the differences in grid generation methods of the software. "Baffle" surfaces were used in Pointwise to control the volume mesh resolution in the wake region to reproduce the source volume clustering used in VGRID. The full scale grid, shown in Figure 1 and Figure 2, had a total cell count of 2.7 million cells, after recombining anisotropic tetrahedral in the boundary layer extrusion to prisms.

The grid was tested first for steady state conditions for a 25 knot wind-over-deck. Once a converged steady state solution was obtained, the grid was tested for unsteady performance at a time step of 0.01 seconds. The unsteady airwake solution is illustrated in Figure 3.

The example input files and grids were provided to PSU. Currently, PSU researchers are running the case to generate 60 second long airwake datasets for performing initial one-way coupled integrations with the GENHEL UH-60 helicopter model.




Figure 1: Full scale SFS2 geometry and grid.




Figure 2: Close-up of volume mesh surrounding the SFS2 ship model.




Figure 3: Velocity contours for the unsteady SFS2 airwake solution.




Figure 4: Isosurface of vorticity colored by velocity for the unsteady SFS2 airwake solution.

2.2 LHD Airwake Case

CRAFT Tech was provided LHD geometry in the form of IGES surfaces and boundary curves for an LHD ship case that had been constructed using the GridTool/VGRID grid generator. A simplified full scale geometry was created by creating triangulated surfaces from the boundary curves using Pointwise. Since the intended grid topology will be structured, the geometry was simplified by removing some of the smaller surfaces such as turrets, elevators, and smaller features on the hull and superstructure.

Initially, a relatively small unstructured grid was generated for this geometry consisting of about 4 million cells, as shown in Figure 5. The case is currently underway and will be presented in the next report. The next step will be to generate a structured grid (target of about 10 million cells) as well as a larger unstructured grid for performance comparisons. The structured LHD calculation, once verified with the "best practices" unstructured calculations, will be the baseline structured calculation for performing speed-up solver development going forward.




Figure 5: LHD geometry and unstructured grid.

3 TECHNICAL/COST STATUS AND PROBLEM AREAS

No technical or financial problems have been encountered.

4 MEETING AND/OR TRAVEL

N/A

5 CONTRACT SCHEDULE

The program is proceeding as planned.

6 PLANNED ACTIVITIES FOR NEXT REPORTING PERIOD

In the next period, initial unstructured calculations will be completed for the LHD airwake case. A structured grid with a target size of 10 million cells will be constructed. Structured calculations with that CRAFT CFD standard solver will be performed and as a baseline solution to compare with larger unstructured calculations.

Discussions with PSU researchers have taken place regarding a plan for integrating GENHEL with the CFD airwake. Initially this will be performed using CRUNCH CFD solutions generated at PSU (for the SFS2 ship calculation) for one-way coupled simulations. Eventually we will progress to fully coupled simulations which will require coordination with NAVAIR to define the communication protocols developed for previous CASTLE/Kestrel coupling.

Report Distribution per CDRLs for Contract No. N00014-13-C-0456

ADDRESSEE Program Officer: Mr. John Kinzer ONR Code 351 Email: john.kinzer@navy.mil	DODAAC CODE N00014	UNCLASSIFIED/ UNLIMITED 1	UNCLASSIFIED/ UNLIMITED 1
Program Officer: Ms. Susan Polsky NAVAIR 4.3.2.1 Email: susan.polsky@navy.mil	N00024	1	1
Administrative Contracting Officer* S3915A	S3915A	1	1
Director, Naval Research Lab Attn: Code 5596 4555 Overlook Ave. SW Washington, D.C. 20375-5320 Email: reports@library.nrl.navy.mil	N00173	1	1
Defense Technical Information Center 8725 John J. Kingman Rd, STE 0944 Ft. Belvoir, VA 22060-6218	НЈ4701	1	1

Email: tr@dtic.mil

ELECTRONIC SUBMISSIONS OF TECHNICAL REPORTS IS PREFERRED AND ENCOURAGED. ELECTONIC SUBMISSION SHOULD BE SENT TO THE EMAIL ADDRESSES PROVIDED IN THE ABOVE TABLE, HOWEVER PLEASE NOTE THE FOLLOWING:

- Only Unlimited/Unclassified document copies may be submitted by email.
- Unclassified/Limited has restricted distribution and a classified document (whether in its entirety or partially) is to be distributed in accordance with classified material handling procedures.
- Electronic submission to DIRECTOR, NAVAL RESEARCH LAB, shall be unclassified./unlimited reports and 30 pages or less. If unclassified and more than 30 pages, hardcopies of reports must be mailed.
- Electronic submission to DTIC shall be unclassified/unlimited reports.

^{*}Send only a copy of the transmittal letter to the Administrative Contracting Officer, do not send actual report to the Administrative Contracting Officer.